

**With smooth walls
Series AS and ASH**

AS
Double insulation

In conformity with
IEC 670-1/94 standards.

Total insulation features
according to EN 60439-1
standard.



Halogen-free materials.

IK08 protection against external
mechanical impacts.



Installation temperature:
-15/ +60°C.

Colour: Grey RAL 7035.

Glow wire test according to IEC
695-2-1:
650° C for series AS
960° C for series ASH



Code	Article	Dimensions	Marks	Pack
------	---------	------------	-------	------

With smooth walls and grey screw-on lids - IP56

35419	AS05	123 x 83 x 62		30
35420	AS15	103 x 103 x 62		100
35421	AS25	154 x 113 x 77		45
35422	AS35	193 x 144 x 79		32
35423	AS45	242 x 190 x 90		20
35424	AS55 •	305 x 225 x 126		10
35425	AS65 •	390 x 310 x 128		4

• Lid fixing by means of plastic screws; box complete of plastic hinge.

With smooth walls and transparent screw-on lids - IP56

35431	AS25T	154 x 113 x 77		45
35432	AS35T	193 x 144 x 79		32
35433	AS45T	242 x 190 x 90		20
35434	AS55T •	305 x 225 x 126		10
35435	AS65T •	390 x 310 x 128		4

• Lid fixing by means of plastic screws; box complete of plastic hinge.


High lid with smooth walls and grey screw-on lids - IP55

35440	ASH15	110 x 110 x 112		80
35441	ASH25	150 x 110 x 150		45
35442	ASH35	150 x 150 x 150		27
35443	ASH45	220 x 150 x 150		24
35444	ASH55	300 x 220 x 150		14

High transparent lid with smooth walls screw-on lids - IP55

35540	ASH15T	110 x 110 x 112		80
35541	ASH25T	150 x 110 x 150		45
35542	ASH35T	150 x 150 x 150		27
35543	ASH45T	220 x 150 x 150		24
35544	ASH55T	300 x 220 x 150		14

Metal plate



Code	Article	Applications	Pack
31334	PB1	for boxes AS3 - 35 - 35T	1
31335	PB2	for boxes AS4 - 45 - 45T	1
31336	PB3	for boxes AS5 - 55 - 55T	1
31337	PB4	for boxes AS6 - 65 - 65T	1
31350	PB5	for boxes ASH15 - ASH15T	1
31351	PB6	for boxes ASH25 - ASH25T	1
31352	PB7	for boxes ASH35 - ASH35T	1
31353	PB8	for boxes ASH45 - ASH45T	1
31354	PB9	for boxes ASH55 - ASH55T	1

With cable glands Series A and AS

Double insulation

In conformity with IEC 670-1/94 standards

Total insulation features according to EN 60439-1 standard.

Halogen-free materials.

IK07 protection against external mechanical impacts.

Installation temperature: -15/ +60°C.

Colour: Grey RAL 7035.

Glow wire test: 650°C according to IEC 695-2-1.



Code	Article	Dimensions	Marks	Pack
With stepped glands and press-fit lids - IP44				
35401	A1	ø 62 x 35 (round)		150
35402	A2	ø 78 x 40 (round)		160
35403	A3	□ 82 x 82 x 40		160

With stepped glands and screw-on lids - IP55



35409	AS0	123 x 83 x 60		50
35410	AS1	103 x 103 x 60		100
35411	AS2	154 x 113 x 75		45
35412	AS3	193 x 144 x 77		24
35413	AS4	244 x 194 x 96		20
35414	AS5 •	305 x 225 x 126		6
35415	AS6 •	388 x 308 x 128		4

• Lid fixing by means of plastic screws; box complete of plastic hinge.

Accessories for series AS



Accessories

31324	VP	Sealable plastic screw for AS5 - AS55 - AS55T - AS6 - AS65 - AS65T	1
-------	----	--	---