


tend ILLUMINATED PUSH BUTTON (Ø22/Ø25/Ø30) ISO 9002

สวิตช์กดมีไฟลือตแลมพ์ชนิดต่อตรง


ชนิดกันน้ำ, กันน้ำมัน, กันฝุ่น IEC 144 IP 65

T2IBS สวิตช์กดมีไฟลือตแลมพ์ดอกเห็ดกดจม 22/25 มม.

T2IKS สวิตช์กดมีไฟลือตแลมพ์ดอกเห็ดกดลือค 22/25 มม.



	Price.
1a,1b,1a1b, 2a	@ n/a
3a,3b,2a2b,4a	@ n/a
3a3b	@ n/a



	Price.
1a,1b,1a1b, 2a	@ n/a
3a,3b,2a2b,4a	@ n/a
3a3b	@ n/a

ILLUMINATED PUSH BUTTON (DIRECT POWER) CONTACT BLOCKS

Type	TC-I1A	TC-I1B	TC-I1C	TC-I2A	
Contact	1a	1b	1a1b	2a	
Contact Arrangement					
Type	TC-I2C	TC-I3A	TC-I3B	TC-I4A	TC-I3C
Contact	2a2b	3a	3b	4a	3a3b
Contact Arrangement					

TYPES OF ILLUMINATED (DIRECT POWER) CONTACT BLOCK AND ASSEMBLY METHOD

Short contact block is available in 1a, 1b. Long contact block is available in 1a1b, 2a. If more contact are needed, just add the short one to the long one (The short one is not designed for being added by other block at its rear end), 2b, 2a2b, 3a, 3b, 4a will be available with one-long-one-short blocks. By replacing the short block with another long one and becoming two-long blocks, 3a3b. will be obtainable.

ILLUMINATED PUSH BUTTON (DIRECT POWER) CONTACT BLOCK DIMENSIONS

คอนแทคบล็อก สำหรับสวิตช์กดมีไฟลือตแลมพ์ในตัว (ชนิดต่อตรง)

<p>TC-I1A, TC-I1B @ n/a</p>	<p>TC-I3A, TC-I3B, TC-I2C, TC-I4A @ n/a</p>
<p>TC-I1C, TC-I2A, TC-I2B @ n/a</p>	<p>TC-I3C @ n/a</p>